

MARTELLI PERFORATORI PNEUMATICI ATLAS COPCO



MODELLO	PESO (Kg)	LUNGHEZZA	RPM	COLPI/MIN	VIBRAZIONI	CONSUMO D'ARIA (6 Bar)
DKR 36	4.5	375 mm	250	2.820	21.2 m/s ²	600 lt/min
BBD 12 D	9.8	565 mm	220	2.580	22.2 m/s ²	1.440 lt/min
BBD 12 DS	10.7	565 mm	220	2.580	22.2 m/s ²	1.320 lt/min
BBD 12 DCS	10.5	560 mm	220	2.580	22.2 m/s ²	1.320 lt/min
BBD 12 T	11.1	505 mm	220	2.580	16 m/s ²	1.440 lt/min
BBD 15 E	15.5	575 mm	220	2.520	7 m/s ²	1.320 lt/min
BBD 15 ET	15.6	575 mm	220	2.520	7 m/s ²	1.320 lt/min
RH 571	17.8	510 mm	190	2.100	23.2 m/s ²	2.340 lt/min
RH 571 S	18.9	510 mm	190	1.980	23.2 m/s ²	2.340 lt/min
RH 572 E	22.8	583 mm	170	2.040	9.7 m/s ²	2.220 lt/min
RH 658	24	565 mm	215	2.040	21.2 m/s ²	3.480 lt/min
RH 658 S	25	565 mm	215	2.020	21.2 m/s ²	3.480 lt/min
SRD 25 E	27	600 mm	250	2.040	10.7 m/s ²	3.000 lt/min
BBC 16 W	28.5	705 mm	-	2.340	16.6 m/s ²	4.140 lt/min